

PR900

DMR Repeater

- 1U Design
- Smart Digital-Analog Auto Detection
- Control Panel With Screen And Button
- IP Connection
- Dispatcher Connection
- Accessory Expansion
- Higher Security and Reliability



Technical Specifications

General	
Digital Protocol	ETSI TS 102 361-1,-2,-3
Frequency	UHF1: 400-470MHz, VHF: 136~174MHz
Channel Capacity	1024
Channel Spacing	12.5KHz/25KHz
Max Duty Cycle	100%
Operating Voltage	AC100 - 240 V @ 50 / 60 Hz DC13.6 V ± 15%
Backup Battery	Support
Size (W x H x D)	483mm x 44.5mm x 366.4mm
Weight	8.5 Kg
Frequency Stability	± 0.5 ppm
Screen	2.0" TFT LCD, 320 x 240
Receiver	
Analog Sensitivity	0.22 μV (12 dB SINAD)
Digital Sensitivity	0.22 μV (5% BER)
Intermodulation	75 dB (TIA603D)
	70 dB (ETSI)
Adjacent Channel Selectivity	65dB@12.5 KHz/70dB@25 KHz (TIA-603D)
	65dB@12.5 KHz/70dB@25 KHz (ETSI)
Spurious Response Rejection	80 dB (TIA603D)
	80 dB (ETSI)
Blocking or Desensitization	90 dB (TIA603D)
	90 dB (ETSI)
FM Hum and Noise	-40 dB@12.5KHz / -45 dB@25KHz
Audio Distortion	≤ 3% (Typical)
Audio Response	+ 1dB ~ - 3 dB
Conducted Spurious Emission	- 57 dBm

Transmitter	
Low Power Output	1W
High Power Output	50W
FM Modulation	12.5KHz:11K0F3E , 25KHz:16K0F3E
4FSK Digital Modulation	12.5KHz Data: 7K60FXD
	12.5KHz Voice & Data:07K60FXE
Conducted/Radiated Emission	-36dBm@≤1GHz , -30dBm@>1GHz
Modulation Limiting	±2.5KHz @12.5KHz /±5.0KHz @25KHz
Adjacent Channel Power	-60dB@12.5KHz , -70dB@25KHz
FM Hum and Noise	-40dB@12.5KHz, - 45dB@25KHz
Environmental	
Operating Temperature	-30 °C ~ + 60 °C
Storage Temperature	-40 °C ~ + 85 °C

Standard Accessories



Add:12F/Building G2, International E-City, Nanshan,Shenzhen,China,518052
 Email: caltta.sales@zte.com.cn Website: www.caltta.com

privacy statement: Caltta Technologies Co.,Ltd. is a leading provider of comprehensive critical communication solutions, the company is committed to protecting personal data by the use of appropriate technical and organisational measures.